

Description:

Coated paper on the front side containing a layer of activated clay.

Colors available: White, yellow, blue, pink, green.

End uses:

Business forms, Invoices

Print methods:

Offset

Certificates:

- [FSC Chain of Custody \(multisite\)](#)
- [PEFC Chain of Custody \(multisite\)](#)
- [EMAS Leitzta mill](#)
- [OHSAS 18001 \(multisite\)](#)



Formula CF

PRODUCT DATA SHEET

Technical specifications

Property	Test Method	Unit	Tolerance	57	60	75	80	90	130	173
Substance	ISO 536	g/m ²	±4%	57	60	75	80	90	130	173
Thickness	ISO 534	µm	g≥130±10	63	66	81	100	113	157	207
Opacity	ISO 2471	%	±4	80	81	85	88	92	95	97
Relative humidity	TAPPI OM -89	T502 %	±5	43	43	43	40	40	40	40
Curl	TAPPI UM-85	T427 mm	(4.0)-0.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0	-2.0

GUARANTEES:

20 years legibility of the copy under normal conditions of storage (T: 15-25 °C and 50-60% RH).
 5 years shelf life under normal conditions of storage and with the original packaging.

Values are subject to change without notice.
 Last update: 07/03/2019